

# Linoleum floor maps

## - Technical features -

Flooring displays are an important addition to any exhibit or visiting place. We offer **linoleum floor maps printed with high quality satellite imagery** of any part of the world.

- ✓ Easy set up with glue or double-sided tape
- ✓ Easy maintenance ; anti-stain treatment
- ✓ Digital printing with UV ink

Technical characteristics	Standard	Measure Unit	Linoleum
Roll width		m	2
Back side			Smooth
Total thickness	EN 428	mm	ca. 1.30
Wearlayer thickness	EN 428	mm	ca. 0.15
Anti-stain treatment			Diamalite (*)
Scratch resistance	EN 660/1	Group	T (excellent)
Weight	EN 430	g/m <sup>2</sup>	ca. 1105
Fire rating	EN ISO 9239-1		Cfl.S <sub>1</sub>
Penetration test	EN 433	mm	0.15
Elongation		%	20
Dimensional stability	EN 434	%	0.05
Load / rupture		daN	10
Sound insulation	EN ISO 717.2	dB	12
Colour fastness	EN 20105-B02	degree	>6
Floor heating	NFT 56124	M <sup>2</sup> KW	suitable
Tearing		daN	2.2

(\*) Diamalite is a special additive within the wearlayer that facilitates cleaning

### Product layer composition :

- 1 – Clear PVC wearlayer
- 2 – Printed, textured, expanded PVC layer
- 3 – Glass fibre interlayer with dimensional stability
- 4 – Extra layer of vinyl